



From Turkey
GLOBAL
28
Different Countries



- www.aygulsondaj.com -

PRODUCT

CATALOG 2022

ADM 500

BEST PRODUCT
BEST SERVICE

Machine Balance: Balance is provided with 4 hydraulic legs.

Kelly: It is 120 mm x 120 mm four corners, 16 mm in thickness, 11 meters in length and can be changed on request.

Water Hoses: 3 "(R2). Absorbent hoses are in a 4-clapper system.

Pulleys: 4 treble for Kelly are 2 to hang. 4 + 2

Hydraulic Pump: 9 pistons, maximum pressure 180 bar.

Machine Equipment: Slip, maneuver head, vise, 8.5 – 12.5 – 17.5 drill shank



Deck Engine: 280 HP Diesel Engine, Transmission 90's Fuller

Tower: The tower top is 14 meters long from 3.5 "pipe and works with 9 roller pulleys.

Chain Box: (Middle Transmitter) 1 input, 7 outputs, 1 "4 rows of double chain, double transmission unit, Rotary gearbox. ZF90, winch gearbox ZF65

Rope Winder: It has 5 + 5, 10 lining system. Ropes are 18 mm thick steel core rope.

Rotary: 230 mm 3/1 rotation speed.

Water Head: Bearing inner diameter 130 mm, outer diameter 250 mm shaft thickness 150 mm, length 600 mm, water head outer diameter 320 mm, water nozzle wedge diameter 130 mm, inner diameter 90 mm

Centrifuge: Large type outlet, 4 "

Welding Machine: 400 Amps



QUALITY
CONFIDENCE
TECHNOLOGY...

ADM
AYGÜL
DRILLING MACHINES



ADM
500



ADM
500



ADM
500



ADM
500



ADM
500



ADM
500

ADM 750

BEST PRODUCT
BEST SERVICE



Machine Balance: 4 hydraulic with feet, balance is achieved.

Kelly: 130 mm x 130 mm Square, original USA 11,5 it's a meter long.

The coolant hoses are: 3 (R2). Suction hoses 4 it's in the klepeli system.

Palangas: 4 for Kelly, TIJ is 3 for hanging. 4 + 2

Hydraulic pump: 9 pistons, maximum pressure 180 bar.

Machine Equipment: Clip, manoeuvring head, vice, 8,5–12,5–17,5 drills handles

Mud pump (DONKY): 6 X 8

Deck Motor: 422 HP Diesel Engine, Sanzuman ZF 85

Tower: Tower 100* 100* 6 mm in profile, 14 meters in length, the tower tower operates with 12 roller bearings.

Chain box: (Center Transmission) 1 in, 7 out, 1 in ¼ 4 row the double chain is fitted with a double shackle unit.

Rope Wrapper: 6+6 is in an air-cooled system with 12 pads. The ropes are 20 mm thick, steel-based rope.

Rotary: 230 mm 3/1 rotation speed.

Water Head: Bearing internal diameter 140 mm, external diameter 250 mm shaft thickness 150 mm, length 600 mm, water head external diameter 320 mm, water head mount diameter 120 mm, internal diameter 80 mm

Centrifugal: Large output, 5

Altarnator: 35 KW



QUALITY
CONFIDENCE
TECHNOLOGY...

ADM
AYGÜL
DRILLING MACHINES



ADM
750



ADM
750



ADM
750



ADM
750



ADM
750



ADM
750

ADM 1000

BEST PRODUCT
BEST SERVICE

Machine Balance: With 4 hydraulic feet, stability is ensured.

Kelly: 140 mm x 130 mm square, Original USA 11,5 meters length.

The coolant hoses are: 3 (R2). Suction hoses with 4-clip in the system.

Palangas: 4 for Kelly, tij it's 3 to hang. 4 + 2

Hydraulic pump: 9 pistons, maximum pressure 180 bar.

Machine Equipment: Clip, manoeuvring head, vice, 8,5–12,5–17,5 drill stalks

Mud pump (DONKY): 7,5 X 10



QUALITY
CONFIDENCE
TECHNOLOGY...



Deck Motor: 422 HP Diesel Engine, 2 PCS

Tower: Tower 100* 100* 6 mm in profile, 14,5 meters in length, the tower tower operates with 12 roller bearings.

Chain box: (Center Transmission) 2 inputs, 7 outputs, 1 ¼ 4 row the double chain is fitted with a double shackle unit.

Rope Wrapper: 4 + 4 = 8 in large lining type system. The ropes are 20 mm thick, steel-based rope.

Rotary: 230 mm 3/1 rotation speed.

Water Head: Bearing internal diameter 140 mm, external diameter 250 mm shaft thickness 150 mm, length 600 mm, water head external diameter 320 mm, water head mount diameter 120 mm, internal diameter 80 mm

Centrifugal: Large output, 5

Alternator: 35 KW

ADM
AYGÜL
DRILLING MACHINES



ADM
1000



ADM
1000



ADM
1000



ADM
1000



ADM
1000



ADM
1000



From Turkey
GLOBAL
28
Different Countries



**QUALITY
CONFIDENCE
TECHNOLOGY...**

info@aygulsondaj.com

www.aygulsondaj.com

0(530) 461 91 88

F. Çakmak Mh Hüda-i Cd Dem-Es San Sit 10620 Sk No:33 KONYA